

The features of E450 are, the unique stylish front door and good cooling as well as the dust proof design, its hand tool free top cover with screwless design reduces time for system integration and maintenance.

It uses SGCC 1.2mm thickness of sheet metal that the edges or the other parts of section designed with no-burrs protection keeping away from hurting hands. The security front door can be also ensured the data will not be leaked by inappropriate access such as DVD burn in or removable USB drive. Additionally, it can be installed with not only regular 12"x9.6"ATX motherboard but also 12"x13" eATX serverboard within 450mm depth of chassis, welcome worldwide distribution.

Specification

- * Totally 10 drive bay: 3 x 5.25" DVD and 7 x 3.5" HDD bay (if MB is 12"x9.6" ATX)
- * Totally 5 drive bay: 1 x 5.25" DVD and 4 x 3.5" HDD bay (if MB is 12"x13" eATX)
- * drive bay equipped with anti-vibration function
- * front butterfly keylock security door with removable dustproof filter
- * with hand tool free screwless top cover (also fix by screws if required)
- * two USB 2.0 ports behind the butterfly keylock front door
- * one Sunon EEC0251B1-000C-G99 120mmx25mm intake fan with dustproof filter at front
- * Room noise without fan activated is 46dBA, tested by 10cm distance to the running fan is 74dBA (including room noise)
- * with plug-in card holder with 6 short-medium-long card clamp (up and down)
- * with 2 ABS plastic easy assembly 80 x 25mm fan frames at rear panel
- * MB: eATX CEB3.61(12"×13")·ATX(12"x9.6")·MicroATX(9.6"x9.6")·Mini-ITX(6.7"x6.7")
- * support PS2 or PS2 Mini-Redundant power supply (max. psu depth at 200mm)
- * support 7 slot full height expansion cards (max. 210mm long)
- * standard paint: black
- * Genesys Group branded server chassis model (with build-in fans) global 3 years warranty
- * chassis dimension: 19" x 4U x 450mm (17.71" deep)
- * package: NW 10KGM, GW 12 KGM, 3.14 CUFT (61x56x26cm, single box packed)

Ordering Information

Model# and description: E450B 4U black enterprise server chassis

Option 1-0: Support PS2 power supply with 80mm~120mm~140mm fan version (max. psu depth: 200mm)

Option 1-1 : SureStar R4B series 400W/500W/600W/700W/800W PS2 Mini Redundant power supply (199mm deep)

Option 1-2: Etasis EFRP-2462 460W PS2 Mini Redundant power supply (190mm deep)

Option 1-3 : Zippy MRT & MRW & MRG series 300W~800W PS2 Mini Redundant power supply (185mm~200mm deep)

Option 1-4: Enhance ENR0500 series 400W or 500W or 600W PS2 Mini Redundant power supply (185mm deep)

Option 2-0 : (NJ-600) 600mm 2-layer 3-travel universal slide rail , full travel extension up to 1100mm deep (part# is 1 pair)

Option 2-1: (1234U-RMK) 1234U rear mounting kit (part# is 1 pair)

Option 3-0 : (SUNON8025) exhaust 80mm x 25mm fan installed at easy assembly ABS fan frame of rear panel (part# is 1pcs)

 $Option \ 4-0: (3U4U-MIDDLEFAN) \ one \ fan \ bracket \ with \ one \ Sunon \ 80mm \ x \ 25mm \ intake \ fan \ installed \ above \ MB \ (part\# is \ 1pcs)$

Option 5-0: (25-35-BK) 5.25" 3.5" 2.5" multiple HDD bracket

Option 6-0: (2525TO3HDBK) 2x5.25" ODD space to 3x3.5" bracket

Option 6-1: (3525TO5HDBK) 3x5.25" ODD space to 5x3.5" bracket

Option 6-2 : (RW425) 1x5.25" to 4x2.5" SAS/SATA Hot-Swap Cage

Option 6-3: (RW825) 2x5.25" to 8x2.5" SAS/SATA Hot-Swap Cage

Option 6-4: (RW1225) 3x5.25" to 12x2.5" SAS/SATA Hot-Swap Cage

Option 6-5 : (RW335) 2x5.25" to 3x3.5" SAS/SATA Hot-Swap Cage

Option 6-6: (RW435) 3x5.25" to 4x3.5" SAS/SATA Hot-Swap Cage

Option 6-7: (RW535) 3x5.25" to 5x3.5" SAS/SATA Hot-Swap Cage

Option 6-8: (TL335) 2x5.25" to 3x3.5" TrayLess SAS/SATA Hot-Swap Cage Option 6-9: (TL435) 3x5.25" to 4x3.5" TrayLess SAS/SATA Hot-Swap Cage

Option 6-10: (TL535) 3x5.25" to 5x3.5" TrayLess SAS/SATA Hot-Swap Cage

Option 6-11 : (TL135) 1x5.25" to 1x3.5" TrayLess SAS/SATA Hot-Swap Cage







