

MINI-ITX 5G LTE-U NAS Desktop or Wallmount solution

MINI-207B is compliant with 5G LTE-U or high speed WiFi networks as well as NAS storage application for enterprises and Soho purpose. It can support one slim ODD and one more 3.5" hard drive with this chassis. This chassis mechanism uses very durable and high end SECC 1.0mm thickness, and the optional wall mount bracket can be installed in harsh industrial environment very well. Cooling system is also equipped with one silent 80mmx25mm fan as standard, and one expansion card via riser as option. Welcome distribution world wide.

Specification

- * Drive bay: 1 x slim ODD, 1 x 3.5" HDD bay
- * Equipped with two USB 2.0 ports behind the front bezel
- * Equipped with one 80mmx25mm silent fan (fan part# D80SM-12)
- * Top cover with thumb screw design for quick system installation
- * SECC 1.0mm high grade sheet metal as durable mechanism
- * Vertical, desktop or wallmount platform allowed (wallmount kit as option)
- * Compatible MB: Mini-ITX 6.7" x 6.7" (170mm x 170mm)
- * Compatible expansion card: 1 slot full height max. 210mm deep (riser card as option)
- * Compatible PSU: standard 1U FlexATX 250W power supply with PFC
- * Standard paint: scratch-resistant Black textured at surface of chassis
- * Genesys Group branded server chassis (with build-in fan) global 3 years warranty
- * Chassis dimension: 257mm x 102mm x 267mm (W x H x D)
- * Accessory Pack: M2 round x4, #6 black round x3, #6 round x8
- * Package: NW 2.3KG, GW 3.5KG, 0.82 CUFT (34x34x20cm, one box packed)

Ordering Information

- Model#: MINI-207B, Black Mini-ITX NAS Desktop/Wallmount chassis
- Option A: Mini-202B-WALL-BK-B, Black wall mount bracket
- Option B: ENP-7025B, 1U FlexATX 250W power supply with PFC
- Option C: 25-35-BK, 5.25" 3.5" 2.5" multiple HDD bracket) (one 3.5" into two 2.5" kit)
- Option D-1: 1U1PCIE1XRC, 1U 1PCI-Express 1X right angle riser card
- Option D-2: 1U1PCIE4XRC, 1U 1PCI-Express 4X right angle riser card
- Option D-3: 1U1PCIE8XRC, 1U 1PCI-Express 8X right angle riser card
- Option D-4: 1U1PCIE16XRC, 1U 1PCI-Express 16X right angle riser card
- Option E-1: JB18A, 1U Intel LGA115x Xeon 1230 active CPU cooler (recommended when expansion card installed)
- Option E-2: JB15C-8080, 1U Intel LGA2011 LGA2066 active CPU cooler (recommended when expansion card installed)
- Option E-3: 1U3647A-R73, 1U Intel LGA3647 active CPU cooler Narrow (recommended when expansion card installed)
- Option E-4: 2U2011A-8080, 2U Intel LGA2011 LGA2066 active CPU cooler Square
- Option E-5: 2U2011A-5694, 2U Intel LGA2011 active CPU cooler Narrow
- Option E-6: 2U1150A, 2U Intel LGA115x Xeon 1230 active CPU cooler
- Option E-7: 2U4094A, 2U AMD EPYC SP3 LGA4094 active CPU cooler
- Option E-8: 2U3647A-S82, 2U Intel LGA3647 active CPU cooler Square
- Option E-9: 2U3647A-R82-1, 2U Intel LGA3647 active CPU cooler Narrow



Latest updated on February 21, 2020