

The era of ATX and MicroATX constructed Multi-Core CPU platforms have been the mainstream nowadays, the fast and stable server system is also presented by this model of design, the major features of this brand new design are, the depth of this chassis has 300mm only, and it can also be installed by standard 19" rackmounting, I/O front-access rackmounting and wallmounting platform all without any extra brackets, it can be also installed two units of C330 at the same 3U space of cabinet's front and rear side with the cost effective and space saving values, combines with two intake 60mm fans at front side as standard and five exhaust 60mm fans at front panel and rear panel and side panel as option, comes with totally 4 drive bay with the chassis configuration, fits all standard 12"x9.6" Intel ATX MB form factor and standard PS2 power supply, meets regular server system application, welcome worldwide distribution.

### Specification

- \* Totally 4 drive bay: 3 x 3.5" HDD bay, 1 x 5.25" ODD (or two 2.5" SSD bay)
- \* Two USB 2.0 at front bezel, Red HDD/Yellow LAN/Green PSU LED, PSU & Reset buttons
- \* Two Sunon EB60251B1-000C-C99 60mmx25mm intake fans with air filter at front bezel
- \* The major sheet metal constructed by 1.2mm thickness SGCC mechanism
- \* Regular I/O rear-access, I/O front-access rackmount, and wallmount compatible
- \* Compatible motherboard: ATX(12"x9.6"), MicroATX(9.6"x9.6"), Mini-ITX(6.7"x6.7")
- \* Support PS2 8cm or 12cm~14cm fan version psu (max. psu depth at 140mm)
- \* 4-slot full height expansion cards at 135mm & 165mm & 217mm deep
- \* Standard paint: scratch-resistant Black textured or scratch-resistant Beige RAL 9018
- \* Genesys Group branded server chassis model (with build-in fan) global 3 years warranty
- \* Chassis dimension: 19" x 3U x 300mm (11.81" deep)
- \* Accessory pack: M3 truss head x 8pcs, #6 round head x 20pcs, Metal MB stand-off x 2pcs
- \* Package: NW 5 KG, GW 7 KG, 1.79 CUFT (55.5x42.5x21.5cm, single box packed)
- \* Suggest to release the rear panel + PS2 PSU set first during system integration
- \* Note: All full height GPU cards with power input on top side will not fit with 3U chassis

### Ordering Information

Model#: C330B, 3U black rackmount wallmount ATX chassis

Option A: PS2 8cm or 12cm~14cm fan version power supply (max. psu depth at 140mm)

Option B: SUNON6025, Five 60mm x 25mm exhaust fans (one for rear panel, two for side panel, two for front panel)

Option C: 25-35-BK, 5.25" 3.5" 2.5" multiple HDD bracket

Option D-1: NJ-600, 600mm 2-layer 3-travel universal rail (cabinet internal depth 600~1200mm compliant)

Option D-2: 1234U-RMK, 1234U rear mounting kit (part# is 1 pair)

Option E-1: RW135-12G, 1x5.25" to 1x3.5" HotSwap Cage SATA/SAS 12G

Option E-2: RW135, 1x5.25" to 1x3.5" HotSwap Cage SATA/SAS 6G

Option E-3: TL135-12G, 1x5.25" ODD to 1x3.5" TrayLess HotSwap Cage SATA/SAS 12G

Option E-4: TL135, 1x5.25" ODD to 1x3.5" TrayLess HotSwap Cage SATA/SAS 6G

Option E-5: RW225-12G, 1x5.25" to 2x2.5" HotSwap Cage SATA/SAS 12G

Option E-6: RW625-12G, 1x5.25" to 6x2.5" HotSwap Cage SATA/SAS 12G

Option E-7: RW825-1525, 1x5.25" to 8x2.5" HotSwap Cage SATA/SAS 6G

Option E-8: RW425-12G-MS, 1x5.25" to 4x2.5" HotSwap Cage SFF-8643 12G

Option E-9: RW425-12G, 1x5.25" to 4x2.5" HotSwap Cage SATA/SAS 12G

Option E-10: RW425, 1x5.25" to 4x2.5" HotSwap Cage SATA/SAS 6G

Option F-1: 1MSAS-4SATA-500MM, SFF-8087 Mini-SAS (Host) to Four SATA (Device) cable

Option F-2: SFF-8643-500MM, SFF-8643 Mini-SAS HD (Host) to SFF-8643 Mini-SAS HD (Device) cable

Option F-3: 4SATA-SFF-8643-500MM, Four SATA (Host) to SFF-8643 Mini-SAS HD (Device) cable

Option F-4: SFF-8643-4SATA-500MM, SFF-8643 Mini-SAS HD (Host) to Four SATA (Device) cable

Option G-1: 2U2011A-8080, 2U Intel LGA2011 active CPU cooler Square (2U 3U 4U chassis compatible)

Option G-2: 2U2011A-5694, 2U Intel LGA2011 active CPU cooler Narrow (2U 3U 4U chassis compatible)

Option G-3: 2U1150A, 2U Intel LGA115x active CPU cooler (2U 3U 4U chassis compatible)

Option G-4: 2U4094A, 2U AMD EPYC SP3 LGA4094 active CPU cooler (2U 3U 4U chassis compatible)

Option G-5: 2U3647A-S82, 2U Intel LGA3647 active CPU cooler Square (2U 3U 4U chassis compatible)

Option G-6: 2U3647A-R82-1, 2U Intel LGA3647 active CPU cooler Narrow (2U 3U 4U chassis compatible)



Latest updated on December 17, 2019