

3U black ATX enterprise server chassis

The most obvious feature of this E339B chassis is its depth 385mm only. In addition, its unique stylish mechanism and excellent ventilation as well as the dust-proof design are also the major characteristics. The main structure made by 1.2mm SGCC ultra high strength sheet metal plate with no sharp corners and burrs. The front security door design also ensure data security and avoid improper burning discs or USB drive to copy data security vulnerabilities caused. This model can be installed in addition to the regular standard ATX 12"x9.6" motherboard, also compatible with the smaller size of server motherboard such as MicroATX and Mini-ITX form factors, for a variety of system environments, the good price competition and the advantage of this chassis design, welcome worldwide distribution.



Specification

- * Totally 9~10 drive bays if MB is 12"x9.6" ATX form factor
2 x 5.25" ODD, 5 x 3.5" HDD, 2 x 2.5" HDD (max. height at 9.5mm)
or 2 x 5.25" ODD, 4 x 3.5" HDD, 2 x 2.5" HDD (max. 9.5mm), 2 x 2.5" HDD (max. 15mm)
- * Totally 10~11 drive bays if MB is 9.6"x9.6" MicroATX or smaller size of MB form factor
3 x 5.25" ODD, 5 x 3.5" HDD, 2 x 2.5" HDD (max. height at 9.5mm)
or 3 x 5.25" ODD, 4 x 3.5" HDD, 2 x 2.5" HDD (max. 9.5mm), 2 x 2.5" HDD (max. 15mm)
- * Drive bay equipped with anti-vibration function, extend storage appliance life
- * Removable front keylock security door with dustproof filter
- * Two USB 3.0 ports behind the front keylock security door (USB 2.0 also compatible)
- * Main structure of SGCC sheet metal thickness at 1.2mm
- * Two 60mmx25mm intake 2ball fans with dustproof filter at front (fan part# DF6025HB1)
- * Room noise w/o fan activated is 45dBA, tested by 10cm distance to running fan is 55dBA (including room noise)
- * Compatible Motherboard: ATX(12"x9.6"), MicroATX(9.6"x9.6"), Mini-ITX(6.7"x6.7")
- * Support PS2 8cm or 12cm~14cm fan version psu (max. psu depth at 140mm~180mm)
- * If 140mm deep PS2 psu installed, 5.25" ODD device by 220mm deep also compatible
- * If 180mm deep PS2 psu installed, 5.25" ODD device by 170mm deep also compatible
- * If front fixed with 3.5" HDD, 4 slot full high plugin cards (max. depth at 170mm)
- * If front fixed w/o 3.5" HDD & bracket, 4 slot full high plugin cards (max. depth at 330mm)
- * Standard paint: black
- * Genesys Group branded server chassis model (with build-in fans) global 3 years warranty
- * Chassis dimension: 19" x 3U x 385mm (15.16" deep)
- * Accessory pack: M3 truss head screw x 8pcs, #6 round head screw x 24pcs, plastic stand-off x 1pcs, metal stand-off x 2pcs, key x 2pcs
- * Package: NW 7 KGM, GW 9 KGM, 2.10 CUFT (54.5x54.5x20cm, one durable carton packed)



Ordering Information

- Model#: E339B, 3U black ATX enterprise server chassis
- Option A: PS2 8cm or 12cm~14cm fan version power supply (max. psu depth at 140mm~180mm)
 - Option B: D60SM-12, Exhaust 60mm x 25mm fan installed above I/O shield (part# is 1pcs, small 3pin x 500mm)
 - Option C-1: NJ-600, 600mm 2-layer 3-travel universal rail (part# is 1 pair, cabinet internal depth 600~1200mm compliant)
 - Option C-2: 1234U-RMK, 1234U rear mounting kit (part# is 1 pair)
 - Option D: 25-35-BK, 5.25" 3.5" 2.5" multiple HDD bracket
 - Option E-1: 2525TO3HDBK, 2x5.25" ODD space to 3x3.5" bracket
 - Option E-2: 3525TO5HDBK, 3x5.25" ODD space to 5x3.5" bracket
 - Option E-3: RW135-12G, 1x5.25" to 1x3.5" HotSwap Cage SATA/SAS 12G
 - Option E-4: RW135, 1x5.25" to 1x3.5" HotSwap Cage SATA/SAS 6G
 - Option E-5: TL135-12G, 1x5.25" ODD to 1x3.5" TrayLess HotSwap Cage SATA/SAS 12G
 - Option E-6: TL135, 1x5.25" ODD to 1x3.5" TrayLess HotSwap Cage SATA/SAS 6G
 - Option E-7: RW225-12G, 1x5.25" to 2x2.5" HotSwap Cage & 4xUSB 3.0 SATA/SAS 12G
 - Option E-8: RW625-12G, 1x5.25" to 6x2.5" HotSwap Cage SATA/SAS 12G
 - Option E-9: RW825-1525, 1x5.25" to 8x2.5" HotSwap Cage SATA/SAS 6G
 - Option E-10: RW425-12G-MS, 1x5.25" to 4x2.5" HotSwap Cage SFF-8643 12G
 - Option E-11: RW425-12G, 1x5.25" to 4x2.5" HotSwap Cage SATA/SAS 12G
 - Option E-12: RW425, 1x5.25" to 4x2.5" HotSwap Cage SATA/SAS 6G
 - Option E-13: RW825, 2x5.25" to 8x2.5" HotSwap Cage SATA/SAS 6G
 - Option E-14: RW335-12G, 2x5.25" to 3x3.5" HotSwap Cage SATA/SAS 12G
 - Option E-15: RW335, 2x5.25" to 3x3.5" HotSwap Cage SATA/SAS 6G
 - Option E-16: TL335-12G, 2x5.25" to 3x3.5" TrayLess HotSwap Cage SATA/SAS 12G
 - Option E-17: TL335, 2x5.25" to 3x3.5" TrayLess HotSwap Cage SATA/SAS 6G
 - Option E-18: RW1225, 3x5.25" to 12x2.5" HotSwap Cage SATA/SAS 6G
 - Option E-19: RW435-12G-MS, 3x5.25" to 4x3.5" HotSwap Cage SFF-8643 12G
 - Option E-20: RW435-12G, 3x5.25" to 4x3.5" HotSwap Cage SATA/SAS 12G
 - Option E-21: RW435, 3x5.25" to 4x3.5" HotSwap Cage SATA/SAS 6G
 - Option E-22: TL435-12G-MS, 3x5.25" to 4x3.5" TrayLess HotSwap Cage SFF-8643 12G
 - Option E-23: TL435-12G, 3x5.25" to 4x3.5" TrayLess HotSwap Cage SATA/SAS 12G
 - Option E-24: TL435, 3x5.25" to 4x3.5" TrayLess HotSwap Cage SATA/SAS 6G
 - Option E-25: RW535-12G, 3x5.25" to 5x3.5" HotSwap Cage SATA/SAS 12G
 - Option E-26: RW535, 3x5.25" to 5x3.5" HotSwap Cage SATA/SAS 6G
 - Option E-27: TL535-12G, 3x5.25" to 5x3.5" TrayLess HotSwap Cage SATA/SAS 12G
 - Option E-28: TL535, 3x5.25" to 5x3.5" TrayLess HotSwap Cage SATA/SAS 6G
 - Option F-1: 1MSAS-4SATA-500MM, SFF-8087 Mini-SAS (Host) to Four SATA (Device) cable
 - Option F-2: SFF-8643-500MM, SFF-8643 Mini-SAS HD (Host) to SFF-8643 Mini-SAS HD (Device) cable
 - Option F-3: 4SATA-SFF-8643-500MM, Four SATA (Host) to SFF-8643 Mini-SAS HD (Device) cable
 - Option F-4: SFF-8643-4SATA-500MM, SFF-8643 Mini-SAS HD (Host) to Four SATA (Device) cable
 - Option G-1: 2U2011A-8080, 2U Intel LGA2011 LGA2066 active CPU cooler Square (2U 3U 4U chassis compatible)
 - Option G-2: 2U2011A-5694, 2U Intel LGA2011 active CPU cooler Narrow (2U 3U 4U chassis compatible)
 - Option G-3: 2U3647A-S82, 2U Intel LGA3647 active CPU cooler Square (2U 3U 4U chassis compatible)
 - Option G-4: 2U3647A-R82-1, 2U Intel LGA3647 active CPU cooler Narrow (2U 3U 4U chassis compatible)

Latest updated on October 02, 2019