

Desktop, MiniTower, Wallmount solution
 Micro ATX motherboard form factor, Intel X99 compliant and Intel LGA1150 platform recommended

The most particular feature of this product is designed as multifunctional applications, the Desktop mode is suitable for enterprise server application, the MiniTower mode also applies to workstation computing applications, the Wallmount mode for industrial controls and NVR surveillance systems (wallmount bracket is option), this chassis can support maximum one slimline ODD and two 2.5" SSD/HDD device. Rugged 1.0mm thickness SGCC sheet metal constructed. Four low profile expansion-cards allowed, welcome for distribution.

Specification

- * Storage space: 1 x slim ODD, 2 x 2.5" SSD/HDD
- * The main sheet metal constructed by 1.0mm thickness SGCC mechanism
- * Front bezel equipped with four USB 2.0, Red HDD/Green Power LED, Power switch
- * Support two 60mmx25mm silent fans at front bezel as option (fan part# D60SM-12C)
- * Compatible MB: MicroATX(9.6"x9.6"), Mini-ITX(6.7"x6.7")
- * Support 4-slot low profile expansion cards up to maximum 200mm deep
- * Support standard 1U FlexATX 250W or 300W power supply (max. psu depth: 150mm)
- * Support wallmount installation as option (part# MICRO-101-WALLBK, one pair)
- * Standard paint: scratch-resistant Black textured or scratch-resistant Beige RAL 9018
- * Genesys Group branded server chassis global 3 years warranty guaranteed
- * Chassis dimension: 300mm x 88mm x 312mm (W x H x D)
- * Accessory pack: M3 truss screw x18pcs, #6 round screw x14pcs, M2 screw x4pcs
- * Package: NW 2.5KG, GW 3.7KG, 1.09 CUFT (42x42x17.5cm, one box packed)



Ordering Information

- Model#: MICRO-101B, Black MicroATX desktop-minitower-wallmount chassis
- Option A: MICRO-101-WALLBK, MICRO-101B black wallmount kit (one pair, thickness 1.6mm, Net weight 0.25KG)
 - Option B: D60SM-12C, YateLoon 60mmx25mm intake fan (part# is 1pcs, can install 2pcs at front bezel)
 - Option C-1: ENP-7025B, 1U FlexATX 250W power supply with PFC (psu size 81.5 x 40.5 x 150/mm)
 - Option C-2: ENP-7130B, 1U FlexATX 300W power supply with PFC (psu size 81.5 x 40.5 x 150/mm)
 - Option D-1: 2U2011A-8080, 2U Intel LGA2011 active CPU cooler Square (2U 3U 4U chassis compatible)
 - Option D-2: 2U2011A-5694, 2U Intel LGA2011 active CPU cooler Narrow (2U 3U 4U chassis compatible)
 - Option D-3: 2U3647A-S82, 2U Intel LGA3647 active CPU cooler Square (2U 3U 4U chassis compatible)
 - Option D-4: 2U3647A-R82-1, 2U Intel LGA3647 active CPU cooler Narrow (2U 3U 4U chassis compatible)

