# Genesys Group ®

Desktop, MiniTower, Wallmount solution
Micro ATX motherboard form factor, Intel X99 compliant and Intel LGA1150 platform recommended

The most particular feature of this product is designed as multifunctional applications, the Desktop mode is suitable for enterprise server application, the MiniTower mode also applies to workstation computing applications, the Wallmount mode for industrial controls and NVR surveillance systems (wallmount bracket is option), this chassis can support maximum one slimline DVDRW and four 2.5" SSD/HDD device. Rugged 1.0mm thickness SGCC sheet metal constructed. Four low profile expansion-cards allowed, welcome for distribution.

## Specification

* Storage space: 1 x slim ODD, 4 x 2.5" SSD/HDD
* The main sheet metal constructed by 1.0mm thickness SGCC mechanism
* Two USB 3.0 at front bezel, Red HDD/Orange LAN/Green PSU LED, PSU/Reset switch
* Equipped with two 80mmx25mm intake silent fans at front (fan part# D80SM-12C)
* Compatible Motherboard: MicroATX(9.6"x9.6"), Mini-ITX(6.7"x6.7")
* Support 4-slot low profile expansion cards up to maximum 280mm deep
* Support standard 1U FlexATX 250W or 300W power supply (max. psu depth: 150mm)
* Support wallmount installation as option (part# Mini-202B-WALL-BK-B, one pair)
* Standard paint: scratch-resistant Black textured or scratch-resistant Beige RAL 9018
* Genesys Group branded server chassis global 3 years warranty guaranteed
* Chassis dimension: 369mm x 88.2mm x 335mm (W x H x D)
* Accessory pack: M3 countersunk x16, #6 truss x13, M2 x4pcs, #6 countersunk x12
* Package: NW 3.0KG, GW 4.2KG, 1.19 CUFT (44x42.5x18cm, one carton packed)

## Ordering Information

Model#: MICRO-103B, Black MicroATX desktop-minitower-wallmount chassis
Option A: MICRO-103B-35BK02, 1x3.5"/2.5" HDD bracket (Front 1 x slim ODD is no longer available, one 3.5" or 2.5" HDD installable)
Option B: MICRO-103B-35BK01, 2x3.5" HDD bracket (MicroATX MB is no longer available, Mini-ITX MB installable)
Option C: Mini-202B-WALL-BK-B, Black wallmount kit with 2mm thickness (one pair, MINI-202B/203B & MICRO-103B compliant)
Option D-1: ENP-7025B, 1U FlexATX 250W power supply with PFC (psu size 81.5 x 40.5 x 150/mm)
Option D-2: ENP-7130B, 1U FlexATX 300W power supply with PFC (psu size 81.5 x 40.5 x 150/mm)
Option E-1: 2U2011A-8080, 2U Intel LGA2011 LGA2066 active CPU cooler Square (2U 3U 4U chassis compatible)
Option E-2: 2U2011A-5694, 2U Intel LGA2011 active CPU cooler Narrow (2U 3U 4U chassis compatible)

MICRO-103B
with 1 x slim ODD bay at front and 4 x 2.5" SSD/HDD bay next to MB as standard configuration of MICRO-103B chassis

MICRO-103B
Option A Part# MICRO-103B-35BK02, Name# 1x3.5"/2.5" HDD bracket

MICRO-103B
Option B Part# MICRO-103B-35BK01, Name# 2x3.5" HDD bracket

Option B

Option A

Latest updated on February 15, 2019