MICRO-104B Black MicroATX desktop-minitower chassis

Desktop, MiniTower NAS Cloud enterprise solution

Micro ATX motherboard compatible, Intel X99 compliant and Intel LGA115x platform recommended

The biggest feature of this design is a multi-functional enterprise server chassis, the desktop mode suitable for small and medium-sized cloud storage server mainframe, the MiniTower mode is also applicable to workstations purposes, with the function of front door keylock is also applicable to enterprises in the data security management, The maximum drive space allows 16 x 2.5-inch hotswap SSD/HDD and 1 x 3.5-inch internal HDD as master drive system, the strength of the use of rugged 1.0mm SGCC steel metal thickness. In addition, it also supports 4 sets of full height and full-size full-length expansion cards at 338.50mm. It's suitable for most of the MicroATX motherboard installation, worldwide distribution welcome.

Specification

- * Five Drive Spaces: 2 x 5.25" ODD, 2 x 3.5" FDD/HDD, 1 x 3.5" HDD
- * The main sheet metal constructed by 1.0mm thickness SGCC mechanism
- Equipped with front door by a security lock & removable dust air filter function
- Two USB 2.0 at front bezel, Red HDD/Orange LAN/Green PSU LED, PSU/Reset switch
- Standard with one brand new 120mmx25mm intake fan at front (fan part# D12SM-12C)
- Compatible Motherboard: MicroATX(9.6"x9.6"), Mini-ITX(6.7"x6.7")
- Compatible 4 slot expansion cards of Full Height & Full-Size 338.50~340.00mm deep
- Equipped with 4 short/long hold-down card clamps upward & downward allowed
- 8cm or 12cm~14cm fan version standard PS2 PSU compatible (depth at 140~260mm)
- Standard paint: scratch-resistant black textured at surface of chassis
- Genesys Group branded server chassis in global 3 years warranty
- Chassis dimension: 177mm x 400mm x 420.50mm (W x H x D)
- * Accessory pack: M5 black fan screw x4, #6 truss screw x25, M3 truss with washer screw x16, M4 nut x1, MB 7mm tall stand-off x9, plugin card guidance x2, black rubber foot x4, hold-down card clamp x4, key x2
- * Package: NW 8.15KG, GW 9.31KG, 2.72 CUFT (carton size 53x50x29cm, one box packed)

Ordering Information

Model#: MICRO-104B, Black MicroATX desktop-minitower chassis

Option A: Support 8cm & 12cm & 14cm fan version PS2 power supply (max. depth at 260mm)

Option B: 25-35-BK, 5.25" 3.5" 2.5" multiple HDD bracket

Option C: 2525TO3HDBK, 2x5.25" ODD space to 3x3.5" bracket

Option D: D60SM-12C, YateLoon 60mmx25mm exhaust fan at small 3pin x 500mm (1pcs at rear)

Option E-1: TL225-12G, 1x3.5" FDD to 2x2.5" TrayLess HotSwap Cage SATA/SAS 12G

Option E-2: TL225, 1x3.5" FDD to 2x2.5" TrayLess HotSwap Cage SATA/SAS 6G

Option E-3: RW135-12G, 1x5.25" to 1x3.5" HotSwap Cage SATA/SAS 12G

Option E-4: RW135, 1x5.25" to 1x3.5" HotSwap Cage SATA/SAS 6G

Option E-5: TL135-12G, 1x5.25" ODD to 1x3.5" TrayLess HotSwap Cage SATA/SAS 12G

Option E-6: TL135, 1x5.25" ODD to 1x3.5" TrayLess HotSwap Cage SATA/SAS 6G
Option E-7: RW225-12G, 1x5.25" to 2x2.5" HotSwap Cage & 4xUSB 3.0 SATA/SAS 12G
Option E-8: RW625-12G, 1x5.25" to 6x2.5" HotSwap Cage SATA/SAS 12G

Option E-9: RW825-1525, 1x5.25" to 8x2.5" HotSwap Cage SATA/SAS 6G

Option E-10: RW425-12G-MS, 1x5.25" to 4x2.5" HotSwap Cage SFF-8643 12G

Option E-11: RW425-12G, 1x5.25" to 4x2.5" HotSwap Cage SATA/SAS 12G

Option E-12: RW425, 1x5.25" to 4x2.5" HotSwap Cage SATA/SAS 6G

Option E-13: RW825, 2x5.25" to 8x2.5" HotSwap Cage SATA/SAS 6G

Option E-14: RW335-12G, 2x5.25" to 3x3.5" HotSwap Cage SATA/SAS 12G

Option E-15: RW335, 2x5.25" to 3x3.5" HotSwap Cage SATA/SAS 6G Option E-16: TL335-12G, 2x5.25" to 3x3.5" TrayLess HotSwap Cage SATA/SAS 12G

Option E-17: TL335, 2x5.25" to 3x3.5" TrayLess HotSwap Cage SATA/SAS 6G

Option F-1: 1MSAS-4SATA-500MM, SFF-8087 Mini-SAS (Host) to Four SATA (Device) cable Option F-2: SFF-8643-500MM, SFF-8643 Mini-SAS HD (Host) to SFF-8643 Mini-SAS HD (Device) cable 12G

Option F-3: 4SATA-SFF-8643-500MM, Four SATA (Host) to SFF-8643 Mini-SAS HD (Device) cable 12G

Option G-1: 2U2011A-8080, 2U Intel LGA2011 LGA2066 active CPU cooler Square (2U 3U 4U chassis compatible)

Option G-2: 2U2011A-5694, 2U Intel LGA2011 active CPU cooler Narrow (2U 3U 4U chassis compatible)









