

# Black Mini-ITX NAS Desktop/Wallmount chassis

MINI-ITX 4G LTE NAS Desktop or Wallmount solution  
 Intel X99 compliant and Intel LGA1150, VIA C series platform recommended

The features of this new Mini-ITX chassis are compliant with 4G LTE or high speed WiFi networks and cloud transmission as well as NAS storage application for enterprises and SOHO purpose. It can support maximum two 2.5" SSD/HDD or one 3.5" hard drive with this chassis. This chassis mechanism uses very durable and high end SGCC 1.0mm thickness, and the optional wall mount bracket can be installed in harsh industrial environment very well. The Cooling system also equipped with one silent 80mmx25mm fan (option). It also supports one expansion card via riser card as well. Welcome distribution world wide.



## Specification

- \* Drive bay:  
 Two 2.5" SSD/HDD bay (one expansion card via riser is available)  
 or one 3.5" HDD bay (one expansion card via riser is not available)
- \* Equipped with two USB 2.0 ports at front bezel (MINI-204B-USB3 if USB 3.0 installed)
- \* SGCC 1.0mm high grade sheet metal works as durable mechanism
- \* Support wallmount bracket (option, part# Mini-202B-WALL-BK-B)
- \* Support one 80mmx25mm silent fan (option, fan part# D80SM-12C)
- \* Support Mini-ITX MB mounting at 6.7" x 6.7" (170mm x 170mm)
- \* One expansion card compatible (max. card depth at 170mm via optional riser card)
- \* If expansion card or 3.5" HDD installed, maximum 40mm high CPU cooler available
- \* If expansion card or 3.5" HDD not installed, maximum 80mm high CPU cooler available
- \* Support standard 1U FlexATX 250W PSU (must use our company's wiring harness)
- \* Standard paint: scratch-resistant Black textured at surface of chassis
- \* Genesys Group branded server chassis in global 3 years warranty
- \* Chassis dimension: 224mm x 88mm x 206mm (W x H x D)
- \* Accessory Pack: M3 truss x6, M3 countersunk x8, #6 black countersunk x4, #6 truss x4, #6 countersunk x6
- \* Package: NW 1.52 KG, GW 1.92 KG, 0.58 CUFT (carton size: 30cm x 18.5cm x 29.5cm)

## Ordering Information

- Model#: MINI-204B, Black Mini-ITX NAS Desktop/Wallmount chassis  
 Model#: MINI-204B-USB3, Black Mini-ITX NAS Desktop/Wallmount chassis (USB 3.0 version)  
 Option A: ENP-7025B, MINI-204B based 1U FlexATX 250W power supply with PFC (psu size 81.5 x 40.5 x 150/mm)  
 Option B: Mini-202B-WALL-BK-B, Black wall mount bracket (one pair as a unit, MINI-202B & MINI-203B & MINI-204B all compatible)  
 Option C: D80SM-12C, 80mmx25mm intake cooling fan (one piece as a unit, can be installed at front bezel)  
 Option D-1: 1U1PCIE4XRC, 1U 1PCI-Express 4X right angle riser card  
 Option D-2: 1U1PCIE8XRC, 1U 1PCI-Express 8X right angle riser card  
 Option D-3: 1U1PCIE16XRC, 1U 1PCI-Express 16X right angle riser card  
 Option E-1: 2U2011A-8080, 2U Intel LGA2011 active CPU cooler Square (available when expansion card & 3.5" HDD not installed)  
 Option E-2: JB15C-8080, 1U Intel LGA2011 active CPU cooler (available when expansion card or 3.5" HDD installed)  
 Option E-3: JB18A, 1U Intel LGA1150 Xeon 1230 active CPU cooler (available when expansion card or 3.5" HDD installed)

