

The Mini-ITX with multi-core processor structure and the newest Intel X99 platform have already the trend nowadays, the most prominent feature of S408B-TWIN-ITX is the compatibility of Dual Mini-ITX motherboards and dual power supplies system, also the 8 sets of 3.5" 6G or 12G hotswap drives as well as four 3.5" internal hard drive space, excellent matching and application of GPU solution. Cooling as standard three 80mmx25mm 2-ball bearing fans the effective cooling system, combines the advantages of multi-functional and competitive price, welcome worldwide distribution.

全ての注目を集め、デュアルMini-ITX+デュアルGPU
+デュアル電源 Super Computer発表



Specification

- * Four internal 3.5" HDD bay:
Two HDD for each system, totally four drives compatible
- * Eight hotswap 3.5" HDD bay (eight hotswap 2.5" HDD/SSD also compatible):
SATA2/SATA3(6G) & SAS-1/SAS-2(6G) HDD, max. 25.4mm height of HDD compatible or MiniSAS HD (12G) HDD, max. 26.1mm height of HDD compatible
(additional RAID Controller Card required)
- * Mobile rack Left LED: Green power LED
- * Mobile rack Right LED: Blue access LED (sold Red light if HDD temp over 60-degree C)
- * Stainless & Hair surface proceeded mobile rack structure with security keylock
- * 2 Hotswap 6G SFF-8087 backplanes: 1 to 4port MiniSAS connector (6G version)
- * 2 Hotswap 12G SFF-8643 backplanes: 1 to 4port MiniSAS HD connector (12G version)
- * Equipped with heavy duty durable aluminum die-casting handles
- * Front bezel equipped with four USB 2.0 ports (two USB 2.0 ports for each system)
- * Three Sunon 80mmx25mm 2ball fans against HDD (fan part# EE80251B1-000C-G99)
- * Room noise without fans activated is 49dBA, tested by 10cm distance to the running fans is 55dBA (including room noise)
- * Support 2 standard 6.7"x6.7" Mini-ITX motherboards (170mm x 170mm)
- * Support 2 one slot full height expansion cards (max. 340mm or 13.39" deep)
- * Support 2 standard PS2 8cm or 12cm~14cm fan version psu (max. depth at 140mm)
- * Major sheet metal by SGCC 1.2mm~2.0mm thickness with no burr & sharp corner design
- * Standard paint: scratch-resistant Black textured at front
- * Genesys Group branded server chassis model (with build-in fans) global 3 years warranty
- * Chassis dimension: 19" x 4U x 618mm (24.33" deep)
- * Accessory pack: key x2, #6 truss x25, M3 truss x10, hotswap cage accessory set x1
- * Package: NW 14 KG, GW 15.5 KG, 4.49 CUFT (75x58.5x29cm, one durable box packed)



Ordering Information

- Model#: S408B-TWIN-ITX, 4U Twin ITX 6G hotswap server chassis (6G version)
- Model#: S408B-TWIN-ITX-12G, 4U Twin ITX 12G hotswap server chassis (12G version)
- Option A: PS2 8cm or 12cm~14cm fan version power supply (max. psu depth at 140mm)
- Option B-1: NJ-S628, 628mm 3-travel slimline slide rail (part# is 1 pair, compatible cabinet external depth 700mm~1000mm)
- Option B-2: SRMK-550, 550mm Slimline rear mounting kit (part# is 1 pair)
- Option C-1: 4SATA-1MSAS-500MM, Four SATA (Host) to SFF-8087 Mini-SAS (Device) cable
- Option C-2: 1MSAS-1MSAS-500MM, SFF-8087 Mini-SAS (Host) to Mini-SAS (Device) cable
- Option C-3: SFF-8643-500MM, SFF-8643 Mini-SAS HD (Host) to SFF-8643 Mini-SAS HD (Device) cable
- Option D-1: 2U2011A-8080, 2U Intel LGA2011 active CPU cooler Square (2U 3U 4U chassis compatible)
- Option D-2: 2U2011A-5694, 2U Intel LGA2011 active CPU cooler Narrow (2U 3U 4U chassis compatible)



Latest updated on December 14, 2017